

# HSR2



## HEAVY STEER REGIONAL

- 23/32" deep improved cut and chip resistant tread compound for optimal performance.
- Patented groove geometry for better resistance to cracking and tearing.
- Protective curb rib for high scrub applications.
- Patented innovative groove technology leads to minimum stone retention extending casing life.
- VAI®+ alerts users of mechanical wear conditions while also indicating removal stage.

### Applications:

Regional hauling and on/off road, all-position.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)*	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5*	G	0568630000	23	75	19.4 (493)	41.6 (1057)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	498 (309)	121 (55)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5*	H	05686310000	23	75	19.4 (493)	41.6 (1057)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	498 (309)	122 (55)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
275/80R22.5*	G	05686340000	23	75	18.7 (475)	40.0 (1016)	11.1 (282)	12.6 (320)	8.25	12.5 (318)	518 (322)	116 (53)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
275/80R22.5*	H	05686350000	23	75	18.6 (472)	40.0 (1016)	11.1 (282)	12.6 (320)	8.25	12.5 (318)	518 (322)	117 (53)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
11R24.5*	G	05686320000	23	75	20.4 (518)	43.5 (1105)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	476 (296)	129 (59)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5*	H	05686330000	23	75	20.4 (518)	43.5 (1105)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	476 (296)	130 (59)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
285/75R24.5*	G	05686360000	23	75	19.4 (493)	41.3 (1049)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	501 (311)	121 (55)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5*	H	05687020000	23	75	19.4 (493)	41.3 (1049)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	501 (311)	121 (55)	6780 (3075)	120 (830)	6175 (2800)	120 (830)

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains.  
\* - ECE Certified  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

# HSR2 Eco Plus



## HEAVY STEER REGIONAL

- Advanced tread compounding provides this Eco Plus version with 20% less rolling resistance than the original HSR2.
- 23/32" deep rolling resistant tread compound for long tread life on highway and regional road combined applications.
- Large radial grooves for improved resistance to groove cracking.
- Sidewall with curb rib reduces damage from curbing, cuts and abrasions.
- Innovative tread geometry helps reduce stone retention and casing penetrations, improving retreadability.
- VAI®+ alerts users of mechanical wear conditions while also indicating removal stage.

### Applications:

Highway and regional hauling, all-position.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)*	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
275/80R22.5*	G	05120840000	23	75	18.7 (475)	40.0 (1016)	11.1 (282)	12.6 (320)	8.25	12.5 (318)	518 (322)	116 (53)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
275/80R22.5*	H	05120850000	23	75	18.6 (472)	40.0 (1016)	11.1 (282)	12.6 (320)	8.25	12.5 (318)	518 (322)	117 (53)	7160 (3250)	120 (830)	6610 (3000)	120 (830)

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains.  
\* - ECE Certified  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.