

HSR2 SA



HEAVY STEER REGIONAL

- Maximum tire life expectancy and wet traction capabilities through customized tread geometry.
- Even tread wear under all load conditions due to optimized contour and balanced pressure distribution.
- Superb wet traction capabilities with minimum wear through innovative tread compound.
- Ideal for buses and larger recreational vehicles.
- VAI®+ alerts users of mechanical wear conditions while also indicating removal stage.

Applications:

Steer or all-position long haul, for bus or large RV traffic.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)*	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (RPM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
275/80R22.5*	H	05120480000	18	75	18.7 (475)	40.0 (1016)	11.1 (282)	12.4 (320)	8.25	12.5 (318)	518 (322)	123 (56)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
295/80R22.5*	H	05120370000	18	81	19.2 (487)	41.8 (1062)	11.4 (290)	12.6 (320)	8.25, 9.00	12.8 (326)	505 (314)	134 (61)	7830 (3550)	120 (830)	6940 (3150)	120 (830)
315/80R22.5*	L	05120980000	20	75	19.7 (500)	43.1 (1094)	12.3 (312)	12.5 (318)	9.00, 9.75	13.8 (351)	491 (305)	142 (64)	9090 (4125)	130 (900)	8270 (3750)	130 (900)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

HSR1



HEAVY STEER REGIONAL

- Tread compound designed to provide long tread life in regional applications.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Tread pattern designed for excellent wet traction and reduced noise.

Applications:

All-position, short and long haul. On/off highway service (depending on conditions).

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)*	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (RPM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
245/70R19.5*	H	05686950000	16	81	15.4 (391)	32.9 (835)	9.8 (249)	10.0 (254)	7.50, 6.75	11.0 (279)	430 (391)	75 (34)	4940 (2240)	120 (830)	4675 (2120)	120 (830)
265/70R19.5*	H	04715400000	17	81	15.8 (401)	34.7 (881)	10.0 (254)	10.4 (264)	6.75	11.2 (286)	608 (378)	78 (35)	5510 (2500)	115 (790)	5205 (2360)	115 (790)
285/70R19.5*	H	04715410000	17	81	16.0 (408)	35.3 (895)	11.1 (283)	12.3 (313)	8.25	12.5 (318)	586 (364)	95 (42)	6395 (2900)	125 (860)	6085 (2725)	125 (860)
305/70R19.5*	J	04715420000	18	81	16.7 (424)	36.3 (923)	11.7 (297)	12.6 (320)	8.25	13.2 (335)	603 (375)	110 (50)	6940 (3150)	125 (860)	6395 (2900)	125 (860)
255/70R22.5*	H	05713450000	18	75	17.0 (433)	36.6 (930)	9.9 (251)	10.8 (274)	8.25, 7.50	11.3 (287)	566 (352)	94 (42)	5510 (2500)	120 (830)	5070 (2300)	120 (830)
275/70R22.5*	J	05120330000	18	81	17.8 (452)	38.0 (966)	11.2 (285)	12.1 (308)	8.25	12.4 (315)	544 (338)	110 (50)	6940 (3150)	130 (900)	6395 (2900)	130 (900)
315/80R22.5*	J	05120440000	19	75	19.7 (500)	42.4 (1076)	12.3 (312)	12.5 (318)	9.00, 8.25	13.9 (355)	491 (305)	140 (63)	8270 (3750)	120 (830)	7385 (3350)	120 (830)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.