

LSR1



LIGHT STEER REGIONAL

- Multi-rib tread design features excellent wet traction, lateral stability and reduced noise.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Advanced tread compound provides long original mileage in regional applications.

Applications:

General rib designs for all-position service. Local delivery, school buses, trailers.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
10R17.5*	H	047120140000	17	75	15.7 (398)	33.8 (858)	10.0 (254)	10.3 (262)	7.5, 6.75	11.3 (286)	613 (381)	70 (32)	4675 (2120)	115 (790)	4410 (2000)	115 (790)
215/75R17.5*	F	04120050000	16	81	14.1 (358)	30.4 (772)	8.5 (216)	9.5 (241)	6.00	9.5 (242)	681 (423)	58 (26)	3750 (1700)	100 (690)	3525 (1600)	100 (690)
235/75R17.5*	F	04714450000	17	81	14.7 (373)	31.9 (811)	9.2 (233)	9.6 (245)	6.75, 7.50	10.3 (262)	662 (412)	67 (31)	4410 (2000)	115 (790)	4190 (1900)	115 (790)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

LSR



LIGHT STEER REGIONAL

- Economical, multi-rib radials designed for even wear, wet traction and high mileage.
- Multi-service tread compound for local and long haul service.
- Solid shoulder design reduces noise and provides even tread wear.

Applications:

Multi-purpose rib designs for all-position service. Local delivery, school buses, trailers.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
8R17.5*	F	04714010000	15	75	14.4 (367)	30.9 (784)	7.6 (193)	7.8 (198)	6.00, 5.25	9.2 (234)	671 (417)	51 (23)	2835 (1285)	85 (590)	2755 (1250)	85 (590)
8.5R17.5*	F	04714020000	15	68	14.7 (374)	31.6 (802)	8.3 (210)	8.5 (216)	6.00	9.5 (242)	656 (407)	55 (25)	3195 (1450)	90 (620)	3085 (1400)	90 (620)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.