

# HSU2



## HEAVY STEER URBAN

- Wider and deeper tread for maximum life in service applications.
- 26/32" deep rib design to provide increased tread life and high removal miles.
- Cut and tear resistant tread compound to provide excellent wear in both high scrub and on/off road applications.
- Enhanced bead design enables 10,000 pound capacity at 65 mph for high load applications.
- Visual Alignment Indicators (VAI®) alert users to tire tracking problems.

### Applications:

Waste haulers, construction and other on/off highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
315/80R22.5*	L	05686450000	26	68	28.1 (510)	43.0 (1093)	12.5 (316)	13.6 (345)	9.00, 8.25	13.8 (351)	481 (299)	153 (69)	10,000 (4540)	130 (900)	9090 (4125)	130 (900)

Note - Rim listed first is the measuring rim.  
 Minimum Dual Spacing calculated without chains.  
 \* - ECE Certified  
 # - Exceeding the lawful speed limit is neither recommended nor endorsed.  
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
 315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi.  
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.  
 When used on an 8.25" rim, the maximum load and pressure is lower than that indicated on the sidewall.

# HSU1



## HEAVY STEER URBAN

- Extra deep tread for long original mileage.
- 5-rib tread pattern provides quiet running with low vibration.
- Reinforced sidewall protects from curbing, cuts, and abrasions.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.

### Applications:

Urban steer/all-position, city buss use.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
275/70R22.5*	H	05725720000	28	62	17.6 (447)	37.8 (961)	10.8 (275)	11.3 (287)	8.25	12.5 (316)	551 (342)	118 (54)	6940 (3150)	125 (860)	6395 (2900)	125 (860)
305/70R22.5*	J	05725760000	26	62	18.2 (463)	39.4 (1000)	11.7 (297)	12.3 (312)	9.00, 8.25	13.5 (340)	528 (328)	126 (57)	7390 (3350)	120 (830)	6940 (3150)	120 (830)

Note - Rim listed first is the measuring rim.  
 Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.  
 \* - ECE Certified  
 # - Exceeding the lawful speed limit is neither recommended nor endorsed.  
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.