

LSU



LIGHT STEER URBAN

- 15/32" multi-service tread compound for local and long-haul service.
- Offset center tread blocks provide excellent all weather traction.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.

Applications:

All position service, waste haulers, construction and other on/off highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
215/75R17.5*	F	0494000000	15	61	14.1 (358)	30.4 (772)	8.5 (215)	9.6 (243)	6.00	9.5 (241)	681 (423)	58 (26)	3750 (1700)	100 (690)	3525 (1600)	100 (690)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Continental Tire The Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

HSC



HEAVY STEER CONSTRUCTION

- Sidewall profile with curb rib reduces damage from curbing, cuts and abrasions.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Visual Alignment Indicators (VAI®) alert user to tire tracking problems.
- 23/32" tread depth and cut/chip resistant tread compound provide long tread life in on/off road conditions.

Applications:

Coal haulers, logging, construction, waste haulers, school buses and other all-position service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5*	H	05683870000	23	68	19.6 (498)	41.9 (1064)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	494 (307)	122 (55)	6610 (3000)	120 (830)	6805 (2725)	120 (830)
12R22.5*	H	05683890000	23	68	20.2 (513)	42.9 (1090)	11.9 (302)	12.5 (318)	9.00	13.5 (343)	483 (300)	138 (63)	7390 (3350)	120 (830)	6780 (3075)	120 (830)
11R24.5	H	05683880000	23	68	20.4 (518)	43.8 (1113)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	473 (294)	131 (59)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
12R24.5	H	05683900000	23	68	20.9 (532)	44.9 (1140)	11.7 (296)	12.8 (325)	9.00	13.5 (343)	461 (287)	149 (67)	7830 (3550)	120 (830)	7160 (3250)	120 (830)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Continental Tire The Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.