

## HMS 45+



## SUPER SINGLE ON/OFF HIGHWAY SERVICE

- Cut and tear resistant compound for efficient on/off highway service.
- Multi-service tread pattern with a combination button and rib-type design for excellent performance.
- 10,000 lb load capacity for high load applications.
- Visual Alignment Indicators (VAI®) alert user to tire tracking problems.

### Applications:

Super single fitment for steer and trailer positions in on/off highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
315/80R22.5	L	05683190000	23	56	19.9 (505)	42.8 (1088)	12.6 (320)	12.9 (328)	9.00	13.8 (351)	483 (300)	136 (62)	10000 (4540)	130 (900)	9090 (4125)	130 (900)

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains.  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

## HDL2 DL



## HEAVY DRIVE LONG-HAUL DEEP LUG

- Deepest tread depth in the industry, a full 32/32nds, providing a long original lifetime and low cost per mile.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Minimized wear and excellent traction over the life of the tire, through a wide, closed shoulder tread and numerous tread blocks with multiple grip edges.
- Increased handling stability through wider casing.

### Applications:

Long haul, over the highway, drive position.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5*	G	05686240000	32	75	19.7 (501)	42.2 (1071)	11.6 (294)	13.0 (329)	8.25	12.5 (318)	491 (305)	138 (63)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5*	H	05687030000	32	75	19.7 (501)	42.2 (1071)	11.6 (294)	13.0 (329)	8.25	12.5 (318)	491 (305)	139 (63)	6430 (3000)	120 (830)	6065 (2725)	120 (830)
275/80R22.5*	G	05686270000	32	75	19.1 (485)	40.8 (1036)	11.4 (289)	12.7 (323)	8.25	12.5 (318)	507 (315)	133 (60)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
11R24.5*	G	05686250000	32	75	20.7 (526)	44.2 (1122)	11.6 (295)	12.5 (318)	8.25	12.5 (318)	468 (291)	147 (67)	6410 (3000)	105 (720)	6065 (2725)	105 (720)
11R24.5*	H	05686260000	32	75	20.7 (526)	44.2 (1122)	11.6 (295)	12.5 (318)	8.25	12.5 (318)	468 (291)	149 (68)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
285/75R24.5*	G	05686280000	32	75	19.7 (501)	42.2 (1073)	11.4 (290)	12.6 (321)	8.25	12.5 (318)	490 (305)	136 (62)	6175 (2800)	110 (760)	5675 (2575)	110 (760)

Note - Rim listed first is the measuring rim.  
\* - ECE Certified  
Minimum Dual Spacing calculated without chains.  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.