

# HDR1



## HEAVY DRIVE REGIONAL

- 28/32" tread depth for long original mileage.
- Open shoulder tread design provides excellent wet/dry traction, resists irregular wear and reduces stone retention.
- Innovative lug angle provides outstanding traction throughout the life of the original tire.

### Applications:

Regional hauling and on/off road.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5*	G	0568670000	28	75	19.5 (495)	41.8 (1062)	11.3 (287)	12.1 (307)	8.25	12.5 (318)	495 (308)	122 (55)	6175 105 (2800 720)	5840 105 (2650 720)		
11R22.5*	H	0568680000	28	75	19.5 (495)	41.8 (1062)	11.3 (287)	12.1 (307)	8.25	12.5 (318)	495 (308)	124 (56)	6610 120 (3000 830)	6005 120 (2725 830)		
275/80R22.5*	G	0568690000	28	75	18.9 (480)	40.8 (1036)	11.0 (279)	12.2 (310)	8.25	12.5 (318)	509 (315)	116 (52)	6175 110 (2800 760)	5675 110 (2575 760)		
275/80R22.5*	H	0568690000	28	75	18.9 (480)	40.8 (1036)	11.0 (279)	12.2 (310)	8.25	12.5 (318)	509 (315)	117 (53)	6940 120 (3150 830)	6175 120 (2800 830)		
11R24.5	G	05686910000	28	75	20.6 (523)	43.8 (1113)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	472 (293)	131 (59)	6610 105 (3000 720)	6005 105 (2725 720)		
11R24.5	H	05686920000	28	75	20.6 (523)	43.8 (1113)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	472 (293)	133 (60)	7160 120 (3250 830)	6610 120 (3000 830)		
285/75R24.5	G	05686930000	28	75	19.6 (498)	42.0 (1066)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	493 (306)	120 (54)	6175 110 (2800 760)	5675 110 (2575 760)		
285/75R24.5	H	05686940000	28	75	19.6 (498)	42.0 (1066)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	493 (306)	121 (55)	6780 120 (3075 830)	6175 120 (2800 830)		

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains.  
\* - ECE Certified  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire The Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

# HDR



## HEAVY DRIVE REGIONAL

- Multi-service tread compound for local and long haul service.
- Offset center tread blocks provide excellent all-weather traction.
- Tapered tread grooves reduce stone retention for long casing life and multiple retreads.

### Applications:

Drive position, short and long haul. On/Off highway service (depending on conditions).

TREAD PATTERN VARIES

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
245/70R19.5*	H	0522020000	20	81	15.3 (389)	33.0 (839)	9.5 (240)	10.4 (264)	6.75	10.6 (270)	627 (389)	71 (32)	4940 115 (2240 790)	4675 115 (2120 790)		
265/70R19.5*	H	04755170000	20	81	15.8 (401)	34.7 (881)	10.0 (254)	10.4 (264)	6.75	11.2 (286)	608 (378)	83 (37)	5510 115 (2500 790)	5205 115 (2360 790)		
285/70R19.5*	H	04755380000	21	81	16.3 (413)	35.2 (895)	10.8 (279)	11.9 (302)	7.50, 8.25	12.2 (309)	588 (365)	88 (40)	6395 125 (2900 860)	6005 125 (2725 860)		
12R22.5	H	05755770000	26	75	19.8 (504)	42.7 (1084)	11.5 (292)	12.1 (307)	8.25, 9.00	13.0 (329)	485 (301)	138 (63)	7830 120 (3550 830)	6940 120 (3150 830)		
255/70R22.5*	H	05753530000	26	81	17.1 (434)	36.6 (930)	10.0 (255)	10.8 (274)	8.25, 7.5	11.3 (287)	565 (351)	97 (44)	5510 120 (2500 830)	5070 120 (2300 830)		
275/70R22.5*	H	05753090000	22	75	17.6 (447)	37.8 (961)	10.6 (270)	11.6 (295)	7.50	12.1 (307)	551 (342)	107 (49)	6940 120 (3150 830)	6395 120 (2900 830)		

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains.  
\* - ECE Certified  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire The Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.