

## HDR 19.5



## HEAVY DRIVE REGIONAL

- 18/32" tread pattern provides excellent traction and long mileage in regional and local service.
- Aggressive tread design provides excellent lateral stability to minimize squirm and improve wet handling performance.
- Open shoulder tread pattern with tie-bar provides even tread wear along with reduced noise and improved traction.
- Original Equipment on Ford F450 and F550.

### Applications:

Regional hauling and on/off road, drive position use.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
225/70R19.5 *	G	04782110000	18	87	15.0 (381)	32.0 (813)	8.6 (218)	9.4 (239)	6.00, 6.75	10.0 (254)	647 (402)	62 (28)	3970 (1800)	110 (760)	3750 (1700)	110 (760)
<small>Note - Rim listed first is the measuring rim.                      Minimum Dual Spacing calculated without chains.                      * - ECE Certified                      † - Exceeding the lawful speed limit is neither recommended nor endorsed.                      Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.                      Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.                      Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.</small>																

## LDR1



## LIGHT DRIVE REGIONAL

- Drive axle tread design features excellent wet traction, lateral stability and reduced noise.
- Balance in tread pattern, compound and design provide outstanding driving characteristics for on/off road service.
- Advanced tread compound provides long original mileage in regional applications.

### Applications:

General rib designs for all-position service. Local delivery and school buses.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
215/75R17.5 *	F	04220040000	20	81	14.2 (361)	30.7 (779)	8.5 (216)	9.6 (244)	6.00	9.5 (241)	675 (420)	62 (28)	3750 (1700)	100 (690)	3525 (1600)	100 (690)
235/75R17.5 *	F	04734450000	21	81	14.7 (373)	31.9 (811)	9.2 (233)	9.6 (245)	6.75, 7.50	10.3 (262)	662 (412)	70 (32)	4410 (2000)	115 (790)	4190 (1900)	115 (790)
<small>Note - Rim listed first is the measuring rim.                      Minimum Dual Spacing calculated without chains.                      * - ECE Certified                      † - Exceeding the lawful speed limit is neither recommended nor endorsed.                      Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.                      Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.                      Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.</small>																