

HDC



HEAVY DRIVE CONSTRUCTION

- Deep 30/32" cut resistant tread provides increased mileage and long wear with no speed restrictions.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Aggressive, self cleaning tread pattern with lateral grooves provides excellent traction in all weather conditions both on and off the road.
- Sidewall profile with curb rib reduces damage from curbing, cuts and abrasions.

Applications:

Coal haulers, logging, construction, waste haulers, school buses and other on/off highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (RPM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
													LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5 *	H	05683940000	30	68	19.6 (498)	42.3 (1074)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	489 (304)	128 (58)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	H	05683950000	30	68	20.6 (524)	47.9 (1206)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	432 (269)	137 (62)	7160 (3250)	120 (830)	6610 (3000)	120 (830)

Note - Rim listed first is the measuring rim.
 Minimum Dual Spacing calculated without chains.
 * - ECC Certified
 † - Exceeding the lawful speed limit is neither recommended nor endorsed.
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

HDO



HEAVY DRIVE OFF-ROAD

- Deep 32/32" tread with cut/chip resistant tread provides excellent traction in off-road conditions.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Sidewall profile with curb rib reduces damage from curbing, cuts and abrasions.

Applications:

Logging, mining, construction and other aggressive, off-road traction needs.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (RPM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
													LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5 *	H	05391190000	32	68	19.7 (500)	42.2 (1072)	11.0 (280)	12.0 (306)	8.25	12.5 (318)	490 (305)	124 (56)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	H	05391200000	32	68	20.6 (524)	44.3 (1124)	11.0 (280)	12.1 (308)	8.25	12.5 (318)	468 (291)	133 (60)	7160 (3250)	120 (830)	6610 (3000)	120 (830)

Note - Rim listed first is the measuring rim.
 Minimum Dual Spacing calculated without chains.
 * - ECC Certified
 † - Exceeding the lawful speed limit is neither recommended nor endorsed.
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.