

HTL1



HEAVY TRAILER LONG HAUL

- 13/32" tread depth minimizes irregular wear.
- Shoulder defense groove provides protection against rapid shoulder wear.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- New sidewall curb rib reduces damage from curbing, cuts and abrasions.
- Scuff ribs protect sidewall from curbing and cutting.

Applications:

Super single fitment for long haul, trailer position in highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
445/50R22.5*	L	05310000000	13	75	18.1 (460)	39.2 (996)	17.3 (439)	19.0 (483)	14.00	NA	528 (328)	179 (81)	10200 (4625)	120 (830)	NA	

* - ECE Certified
 † - Exceeding the lawful speed limit is neither recommended nor endorsed.
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

HTL Eco Plus



HEAVY TRAILER LONG-HAUL

- The Eco Plus product line provides proven fuel economy.
- Visual Alignment Indicators (VAI®) alert user to tire tracking problems.
- Scuff ribs protect sidewall from curbing and cutting.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- 13/32" tread depth minimizes tread squirm and irregular wear.

Applications:

Trailers and free-rolling positions.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5	G	05686730000	13	75	19.3 (490)	41.1 (1044)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	504 (313)	105 (48)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
275/80R22.5	G	05686760000	13	75	18.5 (470)	39.8 (1011)	10.9 (277)	12.0 (305)	8.25	12.5 (318)	520 (323)	100 (45)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
11R24.5	G	05686750000	13	75	20.2 (513)	43.0 (1092)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	481 (299)	113 (51)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
285/75R24.5	G	05686780000	13	75	19.1 (483)	41.1 (1044)	10.9 (277)	12.0 (305)	8.25	12.5 (318)	504 (313)	106 (48)	6175 (2800)	110 (760)	5675 (2575)	110 (760)

Note - Rim listed first is the measuring rim.
 Minimum Dual Spacing calculated without chains.
 † - Exceeding the lawful speed limit is neither recommended nor endorsed.
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.