

# HTR2



## HEAVY TRAILER REGIONAL

- High mileage achieved through precise balance of compound and tread geometry.
- Increased fuel efficiency due to optimized tread pattern and reduced tire weight.
- Tread pattern designed for increased stability and reduced noise.
- Visual Alignment Indicators (VAI®) alert user to tire tracking problems.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.

### Applications:

Local and long haul all-position service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
<b>TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS</b>																
385/65R22.5	L	05320080000	22	75	19.5 (495)	42.0 (1067)	14.8 (376)	16.3 (414)	11.75,12.25	NA	493 (306)	165 (75)	9920 (4500)	130 (900)	NA	
445/65R22.5 *	L	05420030000	22	68	20.6 (524)	46.2 (1174)	17.8 (454)	18.6 (472)	14.00,13.00	NA	462 (287)	200 (91)	12,800 (5800)	130 (900)	NA	

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.  
\* - ECE Certified  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

# HTR1



## HEAVY TRAILER REGIONAL

- Wide tread and advanced tread compound provide long original tread life.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Tread pattern designed for optimized footprint and reduced noise.

### Applications:

Local and long haul trailer position.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
<b>TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS</b>																
265/70R19.5 *	J	04545300000	16	62	15.6 (396)	34.1 (866)	10.7 (272)	11.9 (302)	7.50	11.6 (295)	607 (377)	78 (35)	6005 (2725)	120 (830)	5675 (2575)	120 (830)
285/70R19.5 *	J	04545330000	17	62	16.1 (408)	35.2 (895)	11.3 (288)	12.5 (318)	8.25	12.5 (318)	587 (365)	90 (41)	6940 (3150)	120 (830)	6395 (2900)	120 (830)

Note - Rim listed first is the measuring rim.  
Minimum Dual Spacing calculated without chains.  
\* - ECE Certified  
# - Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.