

# HTR



## HEAVY TRAILER REGIONAL

- High ply ratings provide durability for long casing life and multiple retreads.
- Multiple-rib tread design features excellent wet traction and lateral stability.

### Applications:

Local and long haul trailer position. Super single sizes used in all positions.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION Dual			
													LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
215/75R17.5 *	H	05320120000	15	62	14.1 (359)	30.6 (777)	8.5 (215)	9.3 (236)	6.00	9.5 (242)	676 (420)	62 (28)	4805 (2180)	125 (860)	4540 (2060)	125 (860)
235/75R17.5 *	H	04544320000	16	62	14.7 (373)	31.4 (797)	9.5 (242)	10.0 (254)	6.75	10.6 (270)	660 (410)	65 (30)	6005 (2725)	125 (860)	5675 (2575)	125 (860)
365/80R20 *	L	05721730000	18	68	19.7 (501)	43.0 (1092)	13.7 (347)	15.0 (381)	10.00	NA	482 (299)	155 (70)	9920 (4500)	120 (830)	NA	NA
425/65R22.5 *	L	05723160000	18	68	20.2 (514)	44.3 (1124)	16.6 (422)	18.0 (457)	13.00,14.00	NA	468 (291)	176 (80)	11,400 (5150)	120 (830)	NA	NA

Note - Rim listed first is the measuring rim.  
 Minimum Dual Spacing calculated without chains.  
 \* - ECE Certified  
 † - Exceeding the lawful speed limit is neither recommended nor endorsed.  
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
 8.25R15 can be used with max. inflation 140 psi with high capacity rims.  
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

# HTC1



## HEAVY TRAILER CONSTRUCTION

- Aggressive multi-surface, all-position tread pattern provides excellent traction.
- Cut and tear resistant tread compound for long tread life in on/off road conditions.
- Rugged casing design resists casing penetrations and damage allowing multiple retreads.
- Visual Alignment Indicators (VAI®) alert users to tire tracking problems.
- Outstanding self-cleaning properties ensure a long service life.

### Applications:

Super single fitment for steer and trailer positions in on/off highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION Dual			
													LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
385/65R22.5 *	L	05350990000	23	68	19.5 (495)	42.0 (1067)	14.8 (376)	16.2 (411)	12.25, 11.75	NA	499 (306)	167 (76)	9920 (4500)	130 (900)	NA	NA
445/65R22.5 *	L	05450910000	23	62	20.6 (524)	45.3 (1150)	17.7 (450)	19.1 (485)	14.00,13.00	NA	457 (284)	185 (84)	12,300 (5600)	120 (830)	NA	NA

Note - Rim listed first is the measuring rim.  
 \* - ECE Certified  
 † - Exceeding the lawful speed limit is neither recommended nor endorsed.  
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
 Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.  
 Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.