

HTC



HEAVY TRAILER CONSTRUCTION

- Aggressive multi-surface, all-position tread pattern provides excellent traction in on/off road service.
- Cut and tear resistant tread compound for on/off highway service.
- Thick undertread resists casing penetration and damage for multiple retreads.

Applications:

Super single fitment for steer and trailer positions in on/off highway service.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rims§	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
													LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
275/70R22.5 *	H	05725580000	21	62	17.6 (447)	38.3 (974)	10.8 (275)	11.3 (287)	8.25, 7.50	12.2 (311)	551 (342)	108 (49)	6940 (3150)	125 (868)	6395 (2900)	125 (868)
425/65R22.5 *	L	05753260000	21	68	20.2 (514)	44.3 (1124)	16.6 (422)	18.0 (457)	13.00, 14.00	NA	468 (291)	181 (82)	11,400 (5150)	120 (838)	NA	NA

Note - Rim listed first is the measuring rim.

* - ECE Certified

- Exceeding the lawful speed limit is neither recommended nor enforced.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.