

HSL2



HEAVY STEER LONG-HAUL

- FlexLock™ technology features an interlocking mechanism that promotes even tread wear.
- Advanced compounding with low rolling resistance contributes to optimum fuel efficiency for long haul.
- New, innovative tread compound provides significant increase in removal mileage.
- Visual Alignment Indicators (VAI®) alert user to tire tracking problems.

Applications:

Long haul and over the highway steering and all-position use.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5*	G	0568590000	19	75	19.3 (489)	41.4 (1052)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	500 (311)	117 (53)	LBS 6175 (2800)	PSI 105 (720)	LBS 5840 (2650)	PSI 105 (720)
11R22.5*	H	05686010000	19	75	19.3 (489)	41.4 (1052)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	500 (311)	119 (54)	LBS 6610 (3000)	PSI 120 (830)	LBS 6005 (2725)	PSI 120 (830)
275/80R22.5*	G	05686010000	19	75	18.6 (472)	40.1 (1019)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	516 (321)	112 (51)	LBS 6175 (2800)	PSI 110 (760)	LBS 5675 (2575)	PSI 110 (760)
275/80R22.5*	H	05686050000	19	75	18.6 (472)	40.1 (1019)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	516 (321)	113 (51)	LBS 7160 (3250)	PSI 120 (830)	LBS 6610 (3000)	PSI 120 (830)
11R24.5*	G	05686000000	19	75	20.2 (513)	43.4 (1102)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	477 (296)	125 (57)	LBS 6610 (3000)	PSI 105 (720)	LBS 6005 (2725)	PSI 105 (720)
11R24.5*	H	05686040000	19	75	20.3 (516)	43.4 (1102)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	477 (296)	127 (58)	LBS 7160 (3250)	PSI 120 (830)	LBS 6610 (3000)	PSI 120 (830)
285/75R24.5*	G	05686020000	19	75	19.4 (493)	41.4 (1052)	11.0 (279)	12.0 (305)	8.25	12.5 (318)	500 (311)	115 (52)	LBS 6175 (2800)	PSI 110 (760)	LBS 5675 (2575)	PSI 110 (760)
285/75R24.5*	H	05686060000	19	75	19.4 (493)	41.4 (1052)	11.0 (279)	12.0 (305)	8.25	12.5 (318)	500 (311)	117 (53)	LBS 6780 (3075)	PSI 120 (830)	LBS 6175 (2800)	PSI 120 (830)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

HSL2 Eco Plus



HEAVY STEER LONG-HAUL

- Specialized tread design with wide shoulder ribs and narrow tread grooves.
- Engineered for low noise and optimal weight distribution across tire footprint.
- Long original mileage and optimized rolling resistance.
- Offers large capacity and car carrier trucks the ability to carry more weight without sacrificing vehicle height.

Applications:

Long haul and over the highway steer, for large capacity trucks or car carriers.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)†	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
295/60R22.5*	J	05110040000	17	75	16.8 (427)	37.0 (940)	11.5 (292)	12.0 (304)	9.00	12.9 (328)	561 (348)	105 (48)	LBS 7390 (3350)	PSI 130 (900)	LBS 6780 (3075)	PSI 130 (900)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.