

HSL1 COACH



HEAVY STEER LONG-HAUL

- Superior comfort and quiet running with low vibration.
- 19/32" 5 rib tread pattern offers great handling for maximum safety.
- Low rolling resistance compound and tread design provide excellent fuel economy.
- Evenly-distributed pressure throughout footprint allows for uniform wear and outstanding mileage.
- Premium, all position or steer tire optimized for long distance coaches and recreational vehicles.

Applications:

Long haul, over the highway steering and all-position use.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
315/80R22.5*	L	05687000000	19	75	19.7 (500)	42.4 (1076)	12.3 (312)	12.5 (318)	9.00, 8.25	13.9 (355)	491 (305)	137 (62)	9090 (4125)	130 (900)	8270 (3750)	130 (900)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

HSL Eco Plus



HEAVY STEER LONG-HAUL

- Equal rib widths provide even pressure distribution, resulting in better resistance to irregular wear.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Visual Alignment Indicators (VAI®) alert user to tire tracking problems.
- Tread design provides long mileage and low rolling resistance.

Applications:

Long-haul and over the highway steering and all-position use.

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													Single		Dual	
												LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)	
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
315/80R22.5*	J	05684480000	18	75	19.7 (500)	42.4 (1076)	12.3 (312)	12.9 (328)	9.00, 8.25	13.8 (351)	489 (304)	130 (59)	8270 (3750)	120 (830)	7385 (3350)	120 (830)

Note - Rim listed first is the measuring rim.
Minimum Dual Spacing calculated without chains.
* - ECE Certified
- Exceeding the lawful speed limit is neither recommended nor endorsed.
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lb at 120 psi.
Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations.
Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.